


Plastic Tanks

Stock Sizes

Many other stock sizes available


Bulk Storage Tanks



PVS Series

P/N	170	171	175	177	178	180	181	182	183	184	5050
Gal.	750	1100	1225	1500	1650	550	850	550	1100	1550	2000
Dia. "	80	86	86	86	86	48	48	64	64	64	90
Ht. "	42	54	61	70	70	75	114	47	88	121	84
P/N	5090	5130	5210	5250	5260	5300	5360	5330	5350	5370	5390
Gal.	2500	3000	4400	5600	6200	7000	8750	10500	12500	15000	22000
Dia. "	90	90	90	142	102	142	142	142	142	142	142
Ht. "	103	122	178	101	194	121	144	168	197	233	334


Horizontal Leg Tanks



PHL Series

P/N	106	108	112	128	130	132	136	140	142	146
Gal.	60	30	125	230	750	300	730	525	100	1685
Dia. "	23	23	30	38	46	38	54	48	46	61
Ht. "	39	20	49	52	117	72	80	75	154	159


Horizontal Storage Tanks



PHS Series


P/N	133	137	139	141	143						
Gal.	300	400	500	720	1000						
Dia. "	38	48	48	54	65						
Ht. "	70	64	75	82	87						
						Skids with Cradles Part No.	46200	45300	45400	45500	45600
						Forklift Channels Part No.	46202	46201	46201	46201	46201
						Tank size gal.	300	400	500	720	1000
						Width*	31-5/8	40-5/8	40-5/8	54-5/8	57
						Ht. "	60	48	48	72	86

Conical Bottom Storage Tanks




PCB Series

P/N	188	189	190	191	5070	5110
Gal.	500	1000	1400	1650	2000	2500
Dia. "	86	86	86	86	90	90
Ht. "	42	63	77	92	104	125
P/N	5150	5200	5270	5280	5310	5320
Gal.	3000	4400	6000	6000	7400	7400
Dia. "	90	90	142	142	142	142
Ht. "	143	199	128	133	145	150



Transport Tanks



PHS Series

P/N	161-	159-	161522	159522
D.O.T.	No	No	Yes	Yes
Cap., Gal.	110	175	110	175
Dia. "	22	22	38-1/8	37-7/8
Ht. "	32-1/4	49-1/2	31	48-3/8

Tank Resin Selection Guide – For Tanks up to 22,000 Gallons

	Chemical Resistance General	Stress-Crack Resistance	Maximum Service Temp.	Brittleness Temp.	Impact Temp.	Hot Gas Weldable	FDA Acceptable
HDPE*	VG	G	150°F/65°C	-94°F/-70°C	G	YES	YES
XLPE*	VG	EX	150°F/65°C	-180°F/-118°C	EX	NO	NO

- 296 standard sizes
- Tank diameters from 12" to 142"
- For storage and dispensing of chemicals used in plating, laboratories, photography and water treatment; organic and inorganic acids, caustics, brines, beverages, liquids and foodstuffs

- Rotationally-molded polyethylene construction
- Lightweight, corrosion resistant, easy to maintain
- Available in FDA-Approved tank materials
- Support frames, insulation tank fittings and accessories also available
- Engineering services provided, to help you with your applications

Satisfying Your Tank Requirements — From 15 to 22,000 Gallons