



## STANDARD DESIGN: 650 PSI Vertical Air Receivers with Skirts

Nominal Gallons	Part Number	O.D. Inches	OTH Inches	Actual Gallons	Design Temperature Fahrenheit	MDMT Fahrenheit	Nozzle Size In/Out	Estimated Weight
250	250ARV650	30	90	240	150°	-20°	3"	1,900
600	600ARV650	48	92	600	450°	33°	4"	4,500
800	800ARV650	48	130	800	450°	33°	4"	5,550
1000	1000ARV650	48	144	985	450°	-20°	4"	6,500
1100	1000ARV650	48	155	1,065	450°	-20°	4"	7,000
1500	1500ARV650	48	219	1,500	450°	-20°	4"	9,500
1550	1550ARV650	54	174	1,550	450°	30°	4"	9,500
2000	2000ARV650	60	190	2,060	450°	30°	6"	12,500
2250	2250ARV650L	60	195	2,200	450°	30°	6"	12,500
2250	2250ARV650S	66	174	2,200	450°	33°	6"	14,250
2500	2500ARV650	60	233	2,500	450°	30°	6"	14,500
3000	3000ARV650L	60	285	3,000	450°	30°	6"	17,500
3000	3000ARV650S	66	231	3,000	450°	33°	6"	18,000
4800	4800ARV650	72	300	4,760	320°	35°	6"	28,250
5000	5000ARV650	72	317	5,000	320°	35°	6"	29,750
5500	5500ARV650	72	342	5,400	320°	35°	6"	32,000

### Finish Options:

Epoxy Primer Polyurethane Finish  
Standard 1-Coat Epoxy Lining  
Standard 2-Coat Epoxy Lining  
Food Grade 2-Coat Epoxy Lining

### Notes:

All include 12" x 16" inspection opening & standard red oxide primer. All flange connections shown above are 600#.

### Additional Fittings (Please mark size and quantity of additional fittings for accurate quoting):

NPT Connections 6000# NPT Full Coupling		300# Flanged Connections @ Maximum 325° Fahrenheit		600# Flanged Connections	
Size	Quantity	Size	Quantity	Size	Quantity
1/2"		2"		2"	
3/4"		3"		3"	
1"		4"		4"	
1 1/2"		6"		6"	
2"		8"		8"	
2 1/2"		—		—	
3"		—		—	

# AA tanks